

SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name MONT MARTE ACRYLIC PAINTS 12 PCE (ALL COLOURS EXCEPT BLACK AND BURNT UMBER)
Synonym(s) ACRYLIC PAINT

1.2 Uses and uses advised against

Use(s) PAINTING

1.3 Details of the supplier of the product

Supplier name MONT MARTE INTERNATIONAL PTY LTD
Address 27A Pentex Street, Salisbury, QLD, 4107, AUSTRALIA
Telephone (07) 3255 5406
Fax (07) 3255 5409
Website <http://www.montmarte.net>

1.4 Emergency telephone number(s)

Emergency 13 11 26

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

NOT CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

2.2 Label elements

No signal word, pictograms, hazard or precautionary statements have been allocated.

2.3 Other hazards

No information provided.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
2-AMINO-2-METHYLPROPANOL	124-68-5	-	<1%
2-BROMO-2-NITROPROPANE-1,3-DIOL	52-51-7	200-143-0	<1%
POLYACRYLIC ACID	9003-01-4	-	30 to 50%
2-[(4-CHLORO-2-NITROPHENYL)AZO]-N-(2-CHLOROPHENYL)-3-OXOBUTYRAMIDE	6486-23-3	229-355-1	<30%
C.I. PIGMENT BLUE 29	57455-37-5	611-533-9	<30%
TITANIUM DIOXIDE	13463-67-7	236-675-5	<30%
WATER	7732-18-5	231-791-2	20 to 30%
3-HYDROXY-4-[(2-METHYL-5-NITROPHENYL)AZO]-N-PHENYLNAPHTHALENE-2-CARBOXAMIDE	6448-95-9	229-245-3	<20%
BARIUM SULPHATE	7727-43-7	231-784-4	<20%
CALCIUM 3-HYDROXY-4-[(1-SULPHONATO-2-NAPHTHYL)AZO]-2-NAPHTHOATE	6417-83-0	229-142-3	<20%
IRON HYDROXIDE OXIDE YELLOW	51274-00-1	257-098-5	<20%

PRODUCT NAME MONT MARTE ACRYLIC PAINTS 12 PCE (ALL COLOURS EXCEPT BLACK AND BURNT UMBER)

IRON OXIDE (FE ₂ O ₃)	1309-37-1	215-168-2	<20%
PHTHALOCYANINE GREEN	1328-53-6	215-524-7	<20%
C.I. PIGMENT BLUE 15:4	147-14-8	-	<10%
C.I. PIGMENT ORANGE 13	3520-72-7	222-530-3	<10%
C.I. PIGMENT YELLOW 1	2512-29-0	219-730-8	<10%
HYDROXYETHYL CELLULOSE	9004-62-0	618-387-5	<5%
PROPYLENE GLYCOL (PROPANE-1,2-DIOL)	57-55-6	200-338-0	<5%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
Inhalation	If inhaled, remove from contaminated area. Apply artificial respiration if not breathing.
Skin	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
Ingestion	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once).
First aid facilities	No information provided.

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use an extinguishing agent suitable for the surrounding fire.

5.2 Special hazards arising from the substance or mixture

Combustible. May evolve carbon oxides and hydrocarbons when heated to decomposition.

5.3 Advice for firefighters

Treat as per requirements for surrounding fires. Evacuate area and contact emergency services. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

5.4 Hazchem code

None allocated.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible. Contact emergency services where appropriate.

6.2 Environmental precautions

Prevent product from entering drains and waterways.

6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal. Eliminate all sources of ignition.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

7.2 Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well ventilated area, removed from incompatible substances and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m ³	ppm	mg/m ³
Barium sulphate	SWA (AUS)	--	10	--	--
Iron oxide fume (Fe ₂ O ₃) (as Fe)	SWA (AUS)	--	5	--	--
Propane-1,2-diol (particulates only)	SWA (AUS)	--	10	--	--
Propane-1,2-diol (total vapour & particulates)	SWA (AUS)	150	474	--	--
Titanium dioxide (a)	SWA (AUS)	--	10	--	--

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction ventilation is recommended.

PPE

Eye / Face	When using large quantities or where heavy contamination is likely, wear splash-proof goggles.
Hands	When using large quantities or where heavy contamination is likely, wear PVC or rubber gloves.
Body	When using large quantities or where heavy contamination is likely, wear coveralls.
Respiratory	Not required under normal conditions of use.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance	COLOURED LIQUID
Odour	ODOURLESS
Flammability	CLASS C2 COMBUSTIBLE
Flash point	> 490°C
Boiling point	NOT AVAILABLE
Melting point	NOT AVAILABLE
Evaporation rate	NOT AVAILABLE
pH	8.0 to 9.0
Vapour density	NOT AVAILABLE
Specific gravity	NOT AVAILABLE
Solubility (water)	SOLUBLE
Vapour pressure	NOT AVAILABLE
Upper explosion limit	NOT AVAILABLE
Lower explosion limit	NOT AVAILABLE
Partition coefficient	NOT AVAILABLE
Autoignition temperature	NOT AVAILABLE
Decomposition temperature	NOT AVAILABLE
Viscosity	NOT AVAILABLE

PRODUCT NAME MONT MARTE ACRYLIC PAINTS 12 PCE (ALL COLOURS EXCEPT BLACK AND BURNT UMBER)

9.1 Information on basic physical and chemical properties

Explosive properties	NOT AVAILABLE
Oxidising properties	NOT AVAILABLE
Odour threshold	NOT AVAILABLE

9.2 Other information

Relative density	1.08 to 1.35
------------------	--------------

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Hazardous polymerization is not expected to occur.

10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites) and acids (e.g. nitric acid).

10.6 Hazardous decomposition products

May evolve carbon oxides and hydrocarbons when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Health hazard summary Low toxicity - low irritant. Use safe work practices to avoid eye or skin contact and inhalation. Due to the low vapour pressure of this product, an inhalation hazard is not anticipated with normal use.

Eye Low to moderate irritant. Contact may result in mild irritation, lacrimation and redness.

Inhalation Low to moderate irritant. Over exposure to vapours may result in irritation of the nose and throat, with coughing. High level exposure may result in dizziness, nausea and headache. Due to the low vapour pressure, an inhalation hazard is not anticipated with normal use.

Skin Low irritant. Prolonged or repeated contact may result in mild irritation, rash and dermatitis.

Ingestion Low toxicity. Ingestion may result in gastrointestinal irritation, nausea, vomiting, headache and diarrhoea.

Toxicity data	2-BROMO-2-NITROPROPANE-1,3-DIOL (52-51-7)	
	LC50 (inhalation)	> 5 g/m ³ /6 hours (rat)
	LD50 (ingestion)	180 mg/kg (rat)
	LD50 (intraperitoneal)	26 mg/kg (rat)
	LD50 (intravenous)	37.4 mg/kg (rat)
	LD50 (skin)	1600 mg/kg (rat)
	LD50 (subcutaneous)	116 mg/kg (mouse)
	POLYACRYLIC ACID (9003-01-4)	
	LD50 (ingestion)	2000 mg/kg (guinea pig)
	LD50 (intraperitoneal)	39 mg/kg (mouse)
	LD50 (intravenous)	70 mg/kg (mouse)
	IRON OXIDE (FE2O3) (1309-37-1)	
LDLo (subcutaneous)	30 mg/kg (dog)	
C.I. PIGMENT ORANGE 13 (3520-72-7)		
LD50 (ingestion)	> 5 g/kg (rat)	
PROPYLENE GLYCOL (PROPANE-1,2-DIOL) (57-55-6)		
LD50 (ingestion)	> 2080 mg/kg (quail)	
LD50 (intraperitoneal)	6660 mg/kg	
LD50 (intravenous)	2600 mg/kg (dog)	
LD50 (skin)	20800 mg/kg (rabbit)	

PRODUCT NAME MONT MARTE ACRYLIC PAINTS 12 PCE (ALL COLOURS EXCEPT BLACK AND BURNT UMBER)

PROPYLENE GLYCOL (PROPANE-1,2-DIOL) (57-55-6)	
LD50 (subcutaneous)	17370 mg/kg (mouse)
LDLo (intramuscular)	6300 mg/kg (rabbit)
LDLo (subcutaneous)	15500 mg/kg (guinea pig)
TDL0 (ingestion)	79 g/kg/56 weeks intermittently (child)

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No information provided.

12.2 Persistence and degradability

No information provided.

12.3 Bioaccumulative potential

No information provided.

12.4 Mobility in soil

No information provided.

12.5 Other adverse effects

No information provided.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal For small amounts, absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for additional information if disposing of large quantities (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE, IMDG OR IATA

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	None Allocated	None Allocated	None Allocated
14.2 Proper Shipping Name	None Allocated	None Allocated	None Allocated
14.3 Transport hazard class	None Allocated	None Allocated	None Allocated
14.4 Packing Group	None Allocated	None Allocated	None Allocated

14.5 Environmental hazards No information provided

14.6 Special precautions for user

Hazchem code None Allocated

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous Substances [NOHSC: 1008(2004)].

Hazard codes None allocated.

PRODUCT NAME MONT MARTE ACRYLIC PAINTS 12 PCE (ALL COLOURS EXCEPT BLACK AND BURNT UMBER)

Risk phrases None allocated.

Safety phrases None allocated.

Inventory listing(s) **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**
All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information ACRYLIC - WATER BASED COMPOUNDS: It should be noted that most water based paints and acrylic or thermoplastic resins may contain small percentage of solvents, usually less than 5%. The solvent is used as a dispersion agent for the resin of choice. This solvent component may present potential respiratory hazards only in poorly ventilated areas or when sprayed. Those individuals with existing skin disorders should avoid direct contact.

RESPIRATORS: In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
GHS	Globally Harmonized System
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m ³	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (highly acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

PRODUCT NAME MONT MARTE ACRYLIC PAINTS 12 PCE (ALL COLOURS EXCEPT BLACK AND BURNT UMBER)

Revision history

Revision	Description
3.4	Standard SDS Review.
3.3	Standard SDS Review.
3.2	Standard SDS Review.
3.1	Standard SDS Review.
3.0	Conversion to GHS requirements. Modified supplier address.
2.0	Standard SDS Review.
1.0	Initial SDS creation

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

Prepared by

Risk Management Technologies
5 Ventnor Ave, West Perth
Western Australia 6005
Phone: +61 8 9322 1711
Fax: +61 8 9322 1794
Email: info@rmt.com.au
Web: www.rmt.com.au.

Revision: 3.4
SDS date: 21 January 2015

[End of SDS]